

ELMARK[®]

The Brand of Electricity

TWO & FOUR LINES

SKY TL2032



GENERAL INFORMATION »

- ∴ Rated voltage: 230V/ 50-60Hz
- ∴ Power: 6.5W
- ∴ Colour temperature: 2700K; 4000K; 6400K
- ∴ Colour: White; Black
- ∴ Body: Iron
- ∴ Lampholder: GU10
- ∴ Colour rendering index: Ra≥80
- ∴ Switch on/off: >20 000
- ∴ Long life: 30 000h
- ∴ Protection against dust and moisture: IP40


FEATURES »

- ∴ Completely replace traditional lighting fixtures
- ∴ Pleasant and uniform light distribution
- ∴ Low power consumption
- ∴ Repeated switch on/off does not affect the lifespan
- ∴ Instant light with maximum luminous flux
- ∴ Environmentally friendly - no mercury and lead
- ∴ No ultraviolet and infrared rays
- ∴ Resistant to shock and vibration-free body
- ∴ Low heat emission
- ∴ Suitable for commercial sites, administrative buildings, banks, offices


PRODUCT DETAILS »

Catalogue number WHITE	Catalogue number BLACK	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Length (mm)	Height (mm)
93TL2032/WH	93TL2032/BL	2 LINES EMPTY	-	-	-	55	84	162
93TL2032WW/WH	93TL2032WW/BL	2 LINES	6.5	585	2700	55	84	162
93TL2032W/WH	93TL2032W/BL	2 LINES	6.5	585	4000	55	84	162
93TL2032CW/WH	93TL2032CW/BL	2 LINES	6.5	585	6400	55	84	162
94TL2032/WH	94TL2032/BL	4 LINES EMPTY	-	-	-	55	84	162
94TL2032WW/WH	94TL2032WW/BL	4 LINES	6.5	585	2700	55	84	162
94TL2032W/WH	94TL2032W/BL	4 LINES	6.5	585	4000	55	84	162
94TL2032CW/WH	94TL2032CW/BL	4 LINES	6.5	585	6400	55	84	162



ADDITIONAL INFORMATION »

 **ELMARK**
lighting


93TL2032WW/WH




This luminaire is compatible with bulbs of the energy classes:

The luminaire is sold with a bulb of the energy class:





874/2012

Catalogue number WHITE	Catalogue number BLACK	Packing/B ox (pcs)
93TL2032/WH	93TL2032/BL	1/80
93TL2032WW/WH	93TL2032WW/BL	1/80
93TL2032W/WH	93TL2032W/BL	1/80
93TL2032CW/WH	93TL2032CW/BL	1/80
94TL2032/WH	94TL2032/BL	1/80
94TL2032WW/WH	94TL2032WW/BL	1/80
94TL2032W/WH	94TL2032W/BL	1/80
94TL2032CW/WH	94TL2032CW/BL	1/80

